

# FLUID REFERENCE CHART

## Properties and Applications

LENOX® METALWORKING FLUID	TYPE			METALS				APPLICATIONS					
	FLOOD COOLANT	SPRAY LUBRICANT	MANUAL APPLICATION	USE WITH SOLID METALS	USE WITH STRUCTURAL METALS	USE WITH FERROUS METALS	USE WITH NON-FERROUS METALS	BAND SAWING	CIRCULAR SAWING	DRILLING	TAPPING	MILLING	GRINDING
<i>BAND-ADE</i> ®	•			•	•	•	•	•	•	•		•	
<i>SAW MASTER</i> ™	•			•	•	•		•	•	•			•
<i>LENOX LUBE</i> ®		•		•	•	•		•	•	•	•	•	•
C/AI LUBE		•		•	•	•	•	•	•	•	•	•	•
<i>LENOX PROTOOL LUBE</i> ®			•	•	•	•	•		•	•	•		

LENOX METALWORKING FLUID	CHEMICAL PROPERTIES							
	TYPE	COLOR	BIOCIDES	RUST/CORROSION INHIBITORS	CONTAINS MINERAL OR PETROLEUM OIL	CONTAINS CHLORINE OR SILICONE	CONTAINS SULFUR/SULPHONATES	CONTAINS CARCINOGENS
<i>BAND-ADE</i>	Semi-Synthetic	Translucent Pink	Yes	Yes	No	No	No	No
<i>SAW MASTER</i>	Synthetic	Translucent Pink	Yes	Yes	No	No	No	No
<i>LENOX LUBE</i>	Synthetic Emulsion	Translucent Green	Yes	Yes	No	No	No	No
C/AI LUBE	Synthetic Oil	Translucent Blue	No	Yes	No	No	No	No
<i>LENOX PROTOOL LUBE</i> ®	Synthetic Emulsion	Translucent Yellow	Yes	Yes	No	No	No	No

LENOX METAL REMOVAL FLUID	PHYSICAL PROPERTIES						
	SOLUBILITY IN WATER	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	pH RANGE	VISCOSITY AT 72°F	FLASH POINT	FREEZING POINT	BOILING POINT
<i>BAND-ADE</i>	100%	1.02	8.8 - 9.2	43 SUS	None	-6°C/21°F	99°C/210°F
<i>SAW MASTER</i> ™	100%	1.076	9.7 - 10.0	42.7 SUS	None	-12°C/10°F	99°C/210°F
<i>LENOX LUBE</i>	100%	1.015	7.8 - 8.2	60 SUS	None	-7°C/19°F	99°C/210°F
C/AI LUBE	Insoluble	0.823	N/A	121 SUS	COC 290°F	N/A	N/A
<i>LENOX PROTOOL LUBE</i>	100%	1.03	8.0 - 8.5	500 SUS	None	-25°C/-13°F	99°C/210°F

DILUTION RATIO*	FLUID CONTENT	WATER CONTENT	APPLICATIONS
5:1	20%	80%	Heavy-duty sawing, difficult milling
10:1	10%	90%	Moderate to heavy-duty sawing, drilling, tapping and milling
20:1	5%	95%	Light-duty work
30:1	3%	97%	Grinding, light-duty work

\*Dilution ratios are for flood coolants only. LENOX recommends 5:1 or 10:1, depending on the severity of the operation